



公差表/General Tolerances(mm)		0.1/1.0
0	>3	±0.1
~3	>6	±0.15
~6	10	±0.2
~10	18	±0.25
~18	30	±0.3
~30	50	±0.37
~50	80	±0.45
~80	120	±0.5
~120	180	±0.57
~180	250	±0.63
~250	315	±0.7
~315	400	±0.8
~400	500	±0.9
~500	>500	±1.0
±0.12	±0.18	±0.22
±0.22	±0.26	±0.31
±0.31	±0.37	±0.45
±0.45	±0.57	±0.7
±0.7	±1.05	±1.15
±1.15	±1.60	±2.20
±2.20	±2.50	±2.50

1	Housing	PA66	UL94V-2	
2	Pin header	Copper alloy	Sn Plated	
ITEM	NAME OF PART	MATERIAL	NOTES	
UL 标准/UL Standard: B C D				
额定电压/电流/Rated Voltage(V)/Current(A) 300/15 / 300/10				
EC 标准/EC Standard: 630V/24A				
额定电压/电流/Rated Voltage(V)/Current(A) AC3000				
工频耐受电压(V/Min)/Withstanding Voltage(V/Min) N=02~19P				
使用温度范围/Operating temperature(°C) -40~+75				
符合RoHS环保要求/Conform to RoHS Yes				

MATERIAL: SURFACE:

MAT NO.: /
 STATUS: /
 APPD: Ian CHH 2020.05.18
 CHKD: /
 DRT: jiangx 2013.03.12
 NAME: **DEGSON** 宁波高松电子有限公司
 NINGBO DEGSON ELECTRICAL CO., LTD

DRAWING NO.: 10002006
 SCALE: 2.5:1 SHEET 1/1

REV ECN DESCRIPTION DRT DATE

SIZE: A4 (mm) (inch) TYPE: CUSTOMER DRAWING

1 2 3 4 5 6